

PRODUCT DESCRIPTION

CIRCAMAN™ – RDT Series – Recessed Downlight



FEATURES

- Circadian Rhythm of Light 2800K - 5700K during different time
- Dual Colours - Single Point source LED
- Available in 5W – 30W for 25W – 150W halogen equivalent
- Available multi-beam angle selection 15°/23°/38°/60°
- Selectable CCT - 2800K/3000K/3500K/4000K/4500K/5000K/5700K
- Dimmable to 5%
- Tunable White with Narrow Beam Angle
- Transformer 100-240V 50/60Hz input (Sold separately)
- Android Apps or Optional 2.4GHz Wireless Remote Control

APPLICATIONS

- Display, Hotel, Office, Residential, Restaurant, Retail, Speciality

BENEFITS

- Productivity and concentration improvements
- Improved mood
- Increased customer satisfactory and well-being
- Boost customer dwell time and sale

GENERAL SPECIFICATIONS

Working Voltage –	36V (Typ.) DC input (Light Engine)		
Light Engine	Need to match with our transformer (PSU)		
Working Voltage –	100 – 240 VAC 50/60Hz	Switching	50000x
Transformer (Sold separately)			
Halogen Equivalent	5W – 25W Halogen	Power	Depend on transformer output
(Depend on Transformer)	10W – 50W Halogen		
	15W – 75W Halogen		
	20W – 100W Halogen		
	30W – 150W Halogen		
Operation Temp.	Max. operation temp.		
70°C to 80°C @ Case Temperature	90°C @ Case Temperature		
EU RoHS compliant	YES	Lifetime	35000 hrs – 50000 hrs (nom.)

PRODUCT INFORMATION

Colour temp.	2800K – 5700K		
CRI	90 (Typ.) CRI 80 and 95 on request		
Color Consistency	3 Steps MacAdam @2800K and @5700K		
Selectable CCT:	2800K / 3000K / 3500K / 4000K / 4500K / 5000K / 5700K		
Brightness Setting:	100% / 75% / 50% / 25% / 10% / 5%		
Beam Angle	15° / 23° / 38° / 60°		
Mode: A-Mode (Auto - CCT changing – Constant power)			
C-Mode (Circadian Rhythm - CCT-brightness changing for HCL)			

*CCT selection and Dimming functions by remote control or Android Apps

Lumen output with different wattage PSU (Power supply unit)

Model	5W	10W	15W	20W	30W	40W
RDT75	286 – 334 lm	502 – 588 lm	N.A.	N.A.	N.A.	N.A.
RDT95	320 – 374 lm	621 – 727 lm	875 – 1024 lm	1092 – 1277 lm	N.A.	N.A.
RDT125	333 – 389 lm	640 – 749 lm	932 – 1090 lm	1197 – 1401 lm	1638 – 1916 lm	N.A.

*Lumen output at CCT2800K – CCT5700K. Data for reference only.

DIMENSIONS




Model	Max. Wattage	C - Ceiling Cut-out (mm)	D - Flange Diameter (mm)	H - Height, (mm)
RDT75	Max. 10W	Ø75-80	Ø90	70
RDT95	Max. 20W	Ø95-100	Ø108	85
RDT125	Max. 30W	Ø125-130	Ø135	97

ORDTRING INFORMATION

Example: RDT75-WT-SS-15D-928-957

RDT	75	-	WT	-	SS	-	15D	-	928 - 957
Series	Ceiling Cut-out Diameter	-	Body Colour	-	Reflector Colour	-	Beam Angle	-	Min. CCT – Max. CCT
RDT	75 75-80mm (Max. 10W)		WT White		WT White		15D For 15°		928 – 957 2800K – 5700K@90 CRI *(CRI 80 / 95 on request)
	95 95-100mm (Max. 15W)		BK Black		BK Black		23D For 23°		
	125 125-130mm (Max. 30W)		BK Black		SS Specular Silver		38D For 38°		
							60D For 60°		

AUTO CCT AND BRIGHTNESS CHANGING



Circadian Lighting Limited

contact@circadian-lighting.com

www.circaman.cc

© 2021 Circadian Lighting Limited. All rights reserved.
 For informational purposes only. Content is subject to change.